

HIGH POWER ACTIVE SPEAKERS

SONODYNE®



SPA 1200 SERIES

- Active and passive versions and weatherised versions
- High performance 2 way speaker
- Rigid, unique PP enclosure
- Smooth, wide frequency response
- High sensitivity
- Ideal for mains, fills, stage monitors, FRFR and installation monitors
- Wide Directivity: 90° H x 50° V
- Integrated pole mount for stands and brackets

	SPA 1208	SPA 1210	SPA 1212	SPA 1215
DESCRIPTION	Active 2 way speaker system, ported	Active 2 way speaker system, ported	Active 2 way speaker system, ported	Active 2 way speaker system, ported
TRANSDUCERS: HF	1 x 1" throat compression driver, 1.35" VC	1 x 1" throat compression driver, 1.35" VC	1 x 1" throat compression driver, 1.75" VC	1 x 1" throat compression driver, 1.75" VC
LF	1 x 8" woofer, 150W AES, 1.5" VC	1 x 10" woofer, 250W AES, 2.5" VC	1 x 12" woofer, 300W AES, 2.5" VC	1 x 15" woofer, 400W AES, 3" VC
FREQ. RANGE (-10dB)	60Hz ~ 18kHz	55Hz ~ 18kHz	50Hz ~ 18kHz	50Hz ~ 18kHz
MAX SPL	Continuous: 117dB, Peak: 123dB	Continuous: 120dB, Peak: 126dB	Continuous: 122dB, Peak: 128dB	Continuous: 125dB, Peak: 131dB
POWER	Continuous: 150W, Program: 300W	Continuous: 200W, Program: 400W	Continuous: 300W, Program: 600W	Continuous: 500W, Program: 1000W
INPUTS	2 x MIC/LINE inputs	2 x MIC/LINE inputs	2 x MIC/LINE inputs	2 x MIC/LINE inputs
CONTROLS	2 x Gain controls, 1 Master Level	2 x Gain controls, 1 Master Level	2 x Gain controls, 1 Master Level	2 x Gain controls, 1 Master Level
DIMENSIONS (HxWxD)	420mm x 250mm x 255mm	500mm x 305mm x 310mm	610mm x 360mm x 350mm	700mm x 445mm x 375mm
NET WEIGHT	8.6kg	11.1kg	15.2kg	20.8kg