

SUBWOOFERS

SONODYNE®

SSW SERIES

- 4 models
- Wall, floor and ceiling mount versions
- Both stereo and mono modes
- Inbuilt crossover for high pass to satellite speakers
- Both direct and LMT modes (except SSW 1030)



	SSW 1030	SSW 2010	SSW 2020	SSW 3010
TRANSDUCERS	1 x 10" dual coil subwoofer	1 x 6" dual coil subwoofer	1 x 8" dual voice-coil subwoofer	1 x 6" dual coil sub woofer
NOMINAL IMPEDANCE (direct)	4Ω + 4Ω stereo, 8Ω (in MONO mode)	4Ω + 4Ω stereo, 8Ω (in MONO mode)	4Ω + 4Ω stereo, 8Ω (in MONO mode)	4Ω + 4Ω stereo, 8Ω (in MONO mode)
FREQUENCY RESPONSE (-3dB)	45Hz ~ 180Hz	50Hz ~ 200Hz	45Hz ~ 200Hz	55Hz ~ 150Hz
FREQUENCY RANGE (-10dB)	40Hz ~ 180Hz	45Hz ~ 200Hz	40Hz ~ 200Hz	50Hz ~ 150Hz
SENSITIVITY 1W/1M	95dB	88dB (half space)	90dB (half space)	90dB (half space)
SPL AT RATED POWER	119dB @ 300W	105dB @ 60W	109dB @ 80W	108dB @ 60W
POWER HANDLING (direct, stereo)	300W + 300W	100W + 100W	150W + 150W	100W + 100W
POWER TAPS, 100V (mono)	NA	15W, 30W, 60W	20W, 40W, 80W	15W, 30W, 60W, NA
COLOUR	White/ Black	White/ Black	White/ Black	White/ Black
DIMENSION (HxWxD)	325mm x 580mm x 335mm	350mm x 450mm x 180mm	370mm x 480mm x 225mm	300mm x 205mm (Depth x Dia) Ceiling cut-out: 274mm (Dia)
GROSS WEIGHT	16.5kg	14.7kg	17.1kg	5.3kg
MOUNTING	Wall-mount bracket (included)	Wall-mount bracket (included)	Wall-mount bracket (included)	Ceiling mount