

CA SERIES

column speakers



- 2 models
- 2 way design
- Aluminium cabinet
- Direct and LMT connectivity
- Wall mount provision
- Black/ white colour
- IP 66 rated version available

	CA 410	CA 820
DESCRIPTION	2 way column speaker	2 way column speaker
ENCLOSURE	3mm extruded aluminum	3mm extruded aluminum
GRILL	Perforated nylon	Perforated nylon
TRANSDUCER COMPLEMENTS	4 x 3" pp woofer, 1 x 1" dome tweeter	8 x 3" pp woofer, 1 x 1" dome tweeter
INPUT	Euroblock	Euroblock
SENSITIVITY (1W/ 1M) HALF SPACE	93dB	95dB
NOMINAL IMPEDANCE (DIRECT MODE)	8Ω	4Ω
CROSSOVER FREQUENCY	2.6kHz	1.8kHz
FREQ. RESPONSE (-3dB) (DIRECT MODE)	150Hz ~ 15kHz	140Hz ~ 18kHz
FREQ. RANGE (-10dB) (DIRECT MODE)	120Hz ~ 20kHz	110Hz ~ 20kHz
PROGRAM POWER (DIRECT MODE)	80W	150W
POWER TAPS @ 70V	1.25, 2.5, 5, 10W	3.75, 7.5, 15, 30W
POWER TAPS @ 100V	2.5, 5, 10, 20W	7.5, 15, 30, 60W
DIMENSIONS (HXWXD) MM	579 x 125 x 110	878 x 125 x 110
NET WEIGHT	4kg	6kg
MOUNTING OPTIONS	Swivel bracket (included)	Wall mount (optional)
COLOUR	White/ black	White/ black
WALL MOUNT	A400 WB	A400 WB

Due to continuous improvements, all specifications are subject to change